



SPECIFICATIONS


PUMP SPECIFICATIONS

	U.S.	Metric	
Concrete Output Per Hour (cubic yards-cubic meters)	45	35	
Maximum Pressure on Concrete (psi-bar)	1100	76	
Maximum Aggregate Size (inmm)	1.5	38	
Maximum Horizontal Pumping Distance* (feet-meters)	1160	354	
Maximum Vertical Pumping Distance* (feet-meters)	330	100	
Concrete Cylinder Diameter (inmm)	6	150	
Differential Cylinder Diameter (inmm)	3.14/1.97	80/50	
Concrete Cylinder Stroke Length (inmm)	39	1000	
Maximum Pump Strokes Per Minute	32.5	32.5	
Main Hydraulic Pump	A11V095		
Volume Control	0 to Maximum		
Concrete Valve Type	Long Rock™		
Shifting Cylinders	2		
Hydraulic Tank Capacity (gallon-liters)	50	190	
Hydraulic System	Open Loop		
Hopper-Height (inmm)	48	1220	
Hopper Capacity (cubic feet-cubic meters)	11	.31	
Outlet Diameter (inmm)	5	125	
Engine Model - Tier II	Deutz BF4L2011		
Engine Model - Tier III	Deutz TCD2011 L04i		
Engine Power (horsepower-kilowatt)	72	54	
Fuel Tank Capacity (gallon-liter)	20	75	
Axle	Single Standard		
Axle Capacity Rating (pounds-kilograms)	6000	2722	
Tires	ST 235/80 R16		
Brakes	Electric		
Outrigger Legs	Manual Standard		
Length (incm)	166	422	
Width (incm)	66	168	
Height (incm)	76	193	
Trailer Units Weight (pounds-kilograms)	5500	2495	
Remote Control Cable (feet-meters)	100	30	

^{*}Pumping distances shown are to be used as a guide only since they have been considerably exceeded on specific projects. Maximum attainable distances depend upon concrete mix design and pipeline diameter. Maximum output and distance cannot be achieved simultaneously.

^{**}Pump specifications are for standard units. Other units are available.

Specifications are subject to change without prior notice.




SCHWING-STETTER MOVES CONCRETE. WORLDWIDE.

Wherever concrete is produced and moved is where you will find Schwing-Stetter machinery.

With plants in Germany, Austria, USA, Brazil, Russia, China and India as well as with more than 100 sales and service facilities, the group of companies is always close to the customer.

Our wide range of products with something for every application is what makes Schwing-Stetter the No. 1 system supplier for concrete machinery worldwide.



1/08 - 3M

