


TELEBELT TB 110 SPECIFICATIONS

Conveyors		
Conveyor horizontal reach		
Maximum at 0°	106' 1"	(32.34m)
Maximum at 30°	91' 6"	(27.91m)
Conveyor belt width	18"	(457mm)
Feed conveyor length	38' 0"	(11.60m)
Feed conveyor belt width	18"	(457mm)
Trunk/end hose length	15' 0"	(4.57m)
Discharge height from grade		
Maximum at 30°	60' 2"	(18.36m)
Maximum at -15°	-20' 0"	(-6.11m)
Main & feed conveyors		
Observed capacity at 0°	5.00 yd3/min	(4.00m³/min
Observed capacity at 20°	5.00 yd3/min	(4.00m³/min)
• •	•	
Outriggers		
Net reach beyond outriggers —		
at 0°	100' 6"	(30.65m)
at 30°	86' 0"	(26.23m
Outrigger spread L - R — front manual	23' 1"	(7.05m
out, hydraulic extended down		
Outrigger spread L - R — rear manual	26' 9"	(8.17m
out, hydraulic extended down		
Outrigger spread front to rear	27' 5"	(8.37m)
General Specifications		
Water tank capacity	200 gal	(757L
Hydraulic oil tank capacity	150 gal	(568L
with cooler	150 gai	(5001)
Truck Charifications ***		
Truck Specifications *•+	20 E2E Ibo	/0.210ka
Weight	20,525 lbs	(9,310kg
Engine horsepower	405 hp	(302kW
Wheelbase	299"	(7,595mm
Cab height	104"	(2,642mm
Steering radius (outside)	45' 6"	(13.87m
Steering angle	30°	(000)
Fuel tank capacity	80 gal	(303L
Transmission Mack 1	T310 10-Speed	
Transport Axle Weights *•+		
Steering	19,008 lbs	(8,621kg
Pusher	10,000 lbs	(4,535kg
Tandem	33,754 lbs	(15,309kg
Total	62,762 lbs	(28,465kg)
	02,7 02 100	(20, 100116.

Maximum theoretical values listed.

- * Truck dimensions will vary with different truck makes, models and specifications.
- Weights are approximate and include truck, fuel, and 100 gal (379L) of water.
- + All specifications apply to units mounted on Mack MRU 613.

Photos and drawings are for illustrative purposes only. Authorized Distributor







 Putzmeister America, Inc.
 Phone
 (262) 886-3200

 1733 90th Street
 Toll-free
 (800) 884-7210

 Sturtevant, WI 53177 USA
 Fax
 (262) 884-6338